640~670 Watt

HS 192R-144 BN-DF *Anti-dust* BC Bifacial Modules

Adopts a structural anti-dust frame design, utilizing rainwater to wash away dust

Ideal for high-dust environments and low-tilt installation scenarios



BC Technology

Relocate all electrical contacts to the rear side, eliminating front-side shading to maximize light absorption and power generation.

Anti-Shading Technology

With anti-shading technology, complex environments are no obstacle to generating more power.

Better Weather Adaptability

Excellent low light performance, lower temperature coefficients and power loss under high temperature.

Lower Power Attenuation

Anti-PID and negligible LID/LeTID, which reduces power loss.

Ideal Choice For Utility Project

Lower BOS cost, lower LCOE, and improved ROI.



IEC 61215:2021

IEC 61730:2023

ISO 9001:2015 Quality Management System

ISO 14001:2015 Environmental Management System

ISO 45001:2018 Occupational Health and Safety Management System

CE Marking: European Conformity

15 15-year product warranty

30 30-year linear power output warranty

HEADQUARTER: HORAY SOLAR CO., LTD.

sales@horaysolar.com www.horaysolar.com +86-510 83580688

No.300 Huiming Road, Huishan District, 214177 Wuxi, Jiangsu, P.R. China

GLOBAL MARKETING AND SERVICE: HORAY SOLAR GMBH

info@horaysolar.com www.horaysolar.com

Robert-Bosch-Straße 27-29, 63225 Langen, Germany

HS 192R-144 BN-DF *Anti-dust*

MECHANICAL DIAGRAMS



Unit:mm Tolerance:±2mm

MECHANICAL PARAMETERS

Weight	32.5kg
Dimension	2382×1134×30mm
Cell Orientation	144(6×24)
Junction Box	IP68, three diodes
Output Cable	4mm²,+400,-200mm/±1400mm (length can be customized)
Connector	MC4 compatible
Glass	2.0+2.0mm AR coated heat strengthened glass
Frame	Anodized aluminum alloy frame
Packaging	35pcs per pallet/700pcs per 40'HC

CURVES OF PV MODULE

HS655BN-MHB-D



HS655BN-MHB-D



ELECTRICAL CHARACTERISTICS

Module Type	HS640BN-MHB-D	HS645BN-MHB-D	HS650BN-MHB-D	HS655BN-MHB-D	HS660BN-MHB-D	HS665BN-MHB-D	HS670BN-MHB-D
Testing Condition	STC	STC	STC	STC	STC	STC	STC
Maximum Power(Pmax/W)	640	645	650	655	660	665	670
Open Circuit Voltage(Voc/V)	53.66	53.77	53.89	54.01	54.12	54.24	54.36
Short Circuit Current(Isc/A)	14.87	14.96	15.04	15.12	15.21	15.29	15.37
Maximum Power Voltage(Vmp/V)	45.90	46.00	46.10	46.20	46.30	46.40	46.50
Maximum Power Current(Imp/A)	13.94	14.02	14.10	14.18	14.25	14.33	14.41
Module Efficiency(%)	23.7	23.9	24.1	24.3	24.4	24.6	24.8

* Standard Test Conditions (STC): Irradiance 1000W/m², AM 1.5, Cell temperature 25°C. Power measurement tolerance: ±3%.

ELECTRICAL CHARACTERISTICS WITH DIFFERENT REAR SIDE POWER GAIN (BASED ON 655W)

Pmax/W	Voc/V	Isc/A	Vmp/V	Imp/A	Pmax gain
688	54.03	16.82	46.22	14.89	5%
721	54.05	17.61	46.24	15.59	10%
755	54.07	18.43	46.26	16.32	15%
788	54.09	19.24	46.28	17.03	20%
821	54.11	20.03	46.30	17.73	25%

*Rear side power gain: The additional gain from the rear side compared to the power of the front side at standard test conditions. It depends on mounting (structure, height, tilt angle, etc.) and albedo of the ground.

OPERATING PARAMETERS

Operating Temperature Range	-40°C~+85°C
Power Output Tolerance	0~3%
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	30A
Nominal Module Operating Temperature	45±2°C
[T98]max	≤70°C
Protection Class	Class II
Bifaciality coefficient of Pmax	70±5%
Fire Rating	IEC Class C

MECHANICAL LOADING

Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Hailstone Test	25mm Hailstone at the speed of 23m/s

TEMPERATURE RATINGS (STC)

Temperature Coefficient of Isc	+0.05%/°C
Temperature Coefficient of Voc	-0.20%/°C
Temperature Coefficient of Pmax	-0.26%/°C

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
©2026 Horay Solar Co.,Ltd. All rights reserved.
Specifications included in this datasheet are subject to change without notice.
Version number: HS192R-144BN-DF-2026-A1

YouTube FaceBook Linkedin WeChat