430~450 Watt

HORAY | TIER1 BloombergNEF

HS 210R-96 TC-D *Anti-glare* *N-type Bifacial Modules*

Use high light-transmittance and low-reflection glass to prevent glare

Ideal for glare-sensitive areas such as airports, highways, and residential areas

SMBB Half-Cell Technology
More uniform current distribution, reducing heat loss in internal cells.

Higher Output Power
The output power of 96 half-cell monocrystalline modules is up to 450W.

Mechanical Load Enhanced
Heavy snow load up to 5400 Pa, wind load up to 2400 Pa.

Better Weather Adaptability
Excellent low light performance, lower temperature coefficients and power loss under high temperature.

Lower Power Attenuation
Anti-PID and negligible LID/LeTID, which reduces power loss.

IEC 61215:2021

IEC 61730:2023

ISO 9001:2015 Quality Management System

ISO 14001:2015 Environmental Management System

ISO 45001:2018 Occupational Health and Safety Management System

CE Marking: European Conformity



15 15-year product warranty

30 30-year linear power output warranty

HEADQUARTER: HORAY SOLAR CO., LTD.
sales@horaysolar.com www.horaysolar.com +86-510 83580688
No.300 Huiming Road, Huishan District, 214177 Wuxi, Jiangsu, P.R. China

GLOBAL MARKETING AND SERVICE: HORAY SOLAR GMBH
info@horaysolar.com www.horaysolar.com
Robert-Bosch-Straße 27-29, 63225 Langen, Germany

HS 210R-96 TC-D *Anti-glare*

MECHANICAL DIAGRAMS



Unit:mm Tolerance:±2mm

MECHANICAL PARAMETERS

Weight	24.5kg
Dimension	1762×1134×30mm
Cell Orientation	96 (6×16)
Junction Box	IP68, three diodes
Output Cable	4mm²,±300mm (length can be customized)
Connector	MC4 compatible
Glass	2.0+2.0mm AR coated & Anti-glare heat strengthened glass
Frame	Anodized aluminum alloy frame
Packaging	37pcs per pallet/962pcs per 40'HC

CURVES OF PV MODULE

HS450TC-D-MHC



HS450TC-D-MHC



ELECTRICAL CHARACTERISTICS AT STC

Module Type	HS430TC-MHC-D	HS435TC-MHC-D	HS440TC-MHC-D	HS445TC-MHC-D	HS450TC-MHC-D
Testing Condition	STC	STC	STC	STC	STC
Maximum Power(Pmax/W)	430	435	440	445	450
Open Circuit Voltage(Voc/V)	35.35	35.52	35.69	35.87	36.04
Short Circuit Current(Isc/A)	15.46	15.56	15.66	15.77	15.87
Maximum Power Voltage(Vmp/V)	29.38	29.52	29.66	29.81	29.95
Maximum Power Current(Imp/A)	14.64	14.74	14.83	14.93	15.02
Module Efficiency(%)	21.5	21.8	22.0	22.3	22.5

* Standard Test Conditions (STC): Irradiance 1000W/m², AM 1.5, Cell temperature 25°C. Power measurement tolerance: ±3%.

ELECTRICAL CHARACTERISTICS AT BNPI

Module Type	HS430TC-MHC-D	HS435TC-MHC-D	HS440TC-MHC-D	HS445TC-MHC-D	HS450TC-MHC-D
Testing Condition	BNPI	BNPI	BNPI	BNPI	BNPI
Maximum Power(Pmax/W)	473	479	484	490	495
Open Circuit Voltage(Voc/V)	35.35	35.52	35.69	35.87	36.04
Short Circuit Current(Isc/A)	17.16	17.27	17.39	17.50	17.61
Maximum Power Voltage(Vmp/V)	29.38	29.52	29.66	29.81	29.95
Maximum Power Current(Imp/A)	16.10	16.21	16.32	16.42	16.53

* Bifacial Nameplate Irradiance(BNPI): Irradiance front 1000W/m², rear 135W/m². Power measurement tolerance: ±3%.

OPERATING PARAMETERS

Operating Temperature Range	-40°C~+85°C
Power Output Tolerance	0~3%
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	30A
Nominal Module Operating Temperature	45±2°C
[T98]max	≤70°C
Protection Class	Class II
Bifaciality coefficient of Pmax	80±5%
Fire Rating	IEC Class A

MECHANICAL LOADING

Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Hailstone Test	25mm Hailstone at the speed of 23m/s

TEMPERATURE RATINGS (STC)

Temperature Coefficient of Isc	+0.04%/°C
Temperature Coefficient of Voc	-0.23%/°C
Temperature Coefficient of Pmax	-0.28%/°C

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
©2026 Horay Solar Co.,Ltd. All rights reserved.
Specifications included in this datasheet are subject to change without notice.
Version number: HS210R-TC-D-2026-A1

YouTube FaceBook Linkedin WeChat