430~450 Watt

HORAY | TIER1 BloombergNEF

HS 182-108 TC-D *Ocean* *N-type Bifacial Modules*

SMBB Half-Cell Technology
More uniform current distribution, reducing heat loss in internal cells.

Higher Output Power
The output power of 108 half-cell monocrystalline modules is up to 450W.

Low Light Features
Higher performance under low light environment.

Harsh Environmental Adaptability
Strict salt spray and ammonia corrosion tests by a third party.

Lower Power Attenuation
Anti-PID and negligible LID/LeTID, which reduces power loss.



IEC 61215:2021

IEC 61730:2023

ISO 9001:2015 Quality Management System

ISO 14001:2015 Environmental Management System

ISO 45001:2018 Occupational Health and Safety Management System

CE Marking: European Conformity

CQC: China Quality Certification Centre

Solar Product Certification



15 15-year product warranty

30 30-year linear power output warranty

HEADQUARTER: HORAY SOLAR CO., LTD.
sales@horaysolar.com www.horaysolar.com +86-510 83580688
No.300 Huiming Road, Huishan District, 214177 Wuxi, Jiangsu, P.R. China

GLOBAL MARKETING AND SERVICE: HORAY SOLAR GMBH
info@horaysolar.com www.horaysolar.com
Robert-Bosch-Straße 27-29, 63225 Langen, Germany

HS 182-108 TC-D

MECHANICAL DIAGRAMS



MECHANICAL PARAMETERS

Weight	24.0kg
Dimension	1722×1134×30mm
Cell Orientation	108 (6×18)
Junction Box	IP68, three diodes
Output Cable	4mm², ±1100mm (length can be customized)
Connector	MC4 compatible
Glass	2.0+2.0mm AR coated heat strengthened glass
Frame	Anodized aluminum alloy frame
Packaging	37pcs per pallet/962pcs per 40'HC

CURVES OF PV MODULE

HS450TC-MHO-D



HS450TC-MHO-D



ELECTRICAL CHARACTERISTICS AT STC

Module Type	HS430TC-MHO-D	HS435TC-MHO-D	HS440TC-MHO-D	HS445TC-MHO-D	HS450TC-MHO-D
Testing Condition	STC	STC	STC	STC	STC
Maximum Power(Pmax/W)	430	435	440	445	450
Open Circuit Voltage(Voc/V)	39.30	39.50	39.70	39.90	40.10
Short Circuit Current(Isc/A)	14.15	14.22	14.30	14.37	14.45
Maximum Power Voltage(Vmp/V)	32.84	33.04	33.24	33.44	33.64
Maximum Power Current(Imp/A)	13.10	13.17	13.24	13.31	13.38
Module Efficiency(%)	22.0	22.3	22.5	22.8	23.0

* Standard Test Conditions (STC): Irradiance 1000W/m², AM 1.5, Cell temperature 25°C. Power measurement tolerance: ±3%.

ELECTRICAL CHARACTERISTICS AT BNPI

Module Type	HS430TC-MHO-D	HS435TC-MHO-D	HS440TC-MHO-D	HS445TC-MHO-D	HS450TC-MHO-D
Testing Condition	BNPI	BNPI	BNPI	BNPI	BNPI
Maximum Power(Pmax/W)	474	479	485	490	495
Open Circuit Voltage(Voc/V)	39.30	39.50	39.70	39.90	40.10
Short Circuit Current(Isc/A)	15.56	15.64	15.73	15.81	15.89
Maximum Power Voltage(Vmp/V)	32.84	33.04	33.24	33.44	33.64
Maximum Power Current(Imp/A)	14.43	14.50	14.59	14.65	14.71

* Bifacial Nameplate Irradiance(BNPI): Irradiance front 1000W/m², rear 135W/m². Power measurement tolerance: ±3%.

OPERATING PARAMETERS

Operating Temperature Range	-40°C~+85°C
Power Output Tolerance	0~3%
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	25A
Nominal Module Operating Temperature	45±2°C
[T98]max	≤70°C
Protection Class	Class II
Bifaciality coefficient of Pmax	80±5%
Fire Rating	IEC Class A

MECHANICAL LOADING

Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Hailstone Test	25mm Hailstone at the speed of 23m/s

TEMPERATURE RATINGS (STC)

Temperature Coefficient of Isc	+0.04%/°C
Temperature Coefficient of Voc	-0.23%/°C
Temperature Coefficient of Pmax	-0.28%/°C

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
©2026 Horay Solar Co.,Ltd. All rights reserved.
Specifications included in this datasheet are subject to change without notice.
Version number: HS182-TC-D-2026-A1

YouTube FaceBook Linkedin WeChat