480~500 Watt

HORAY | TIER1 BloombergNEF

HS 182-120 TC Ocean *N-type Mono-facial Modules*

SMBB Half-Cell Technology
More uniform current distribution, reducing heat loss in internal cells.

Higher Output Power
The output power of 120 half-cell monocrystalline modules is up to 500W.

Low Light Features
Higher performance under low light environment.

Harsh Environmental Adaptability
Strict salt spray and ammonia corrosion tests by a third party.

Lower Power Attenuation
Anti-PID and negligible LID/LeTID, which reduces power loss.



IEC 61215:2021

IEC 61730:2023

ISO 9001:2015 Quality Management System

ISO 14001:2015 Environmental Management System

ISO 45001:2018 Occupational Health and Safety Management System

CE Marking: European Conformity

CQC: China Quality Certification Centre

Solar Product Certification



12 12-year product warranty

30 30-year linear power output warranty

HEADQUARTER: HORAY SOLAR CO., LTD.
sales@horaysolar.com www.horaysolar.com +86-510 83580688
No.300 Huiming Road, Huishan District, 214177 Wuxi, Jiangsu, P.R. China

GLOBAL MARKETING AND SERVICE: HORAY SOLAR GMBH
info@horaysolar.com www.horaysolar.com
Robert-Bosch-Straße 27-29, 63225 Langen, Germany

HS 182-120 TC

MECHANICAL DIAGRAMS



Unit:mm Tolerance:±2mm

MECHANICAL PARAMETERS

Weight	23.0kg
Dimension	1909×1134×30mm
Cell Orientation	120 (6×20)
Junction Box	IP68, three diodes
Output Cable	4mm², ±1100mm (length can be customized)
Connector	MC4 compatible
Glass	3.2mm AR coated tempered glass
Frame	Anodized aluminum alloy frame
Packaging	37pcs per pallet/888pcs per 40'HC

MECHANICAL PARAMETERS

HS500TC-MHO



HS500TC-MHO



ELECTRICAL CHARACTERISTICS AT STC

Module Type	HS480TC-MHO	HS485TC-MHO	HS490TC-MHO	HS495TC-MHO	HS500TC-MHO
Testing Condition	STC	STC	STC	STC	STC
Maximum Power(Pmax/W)	480	485	490	495	500
Open Circuit Voltage(Voc/V)	43.26	43.46	43.66	43.86	44.06
Short Circuit Current(Isc/A)	14.22	14.30	14.37	14.43	14.50
Maximum Power Voltage(Vmp/V)	36.44	36.64	36.84	37.04	37.24
Maximum Power Current(Imp/A)	13.17	13.23	13.31	13.36	13.43
Module Efficiency(%)	22.2	22.4	22.6	22.9	23.1

* Standard Test Conditions (STC): Irradiance 1000W/m², AM 1.5, cell temperature 25°C. Power measurement tolerance: ±3%.

ELECTRICAL CHARACTERISTICS AT NMOT

Module Type	HS480TC-MHO	HS485TC-MHO	HS490TC-MHO	HS495TC-MHO	HS500TC-MHO
Testing Condition	NMOT	NMOT	NMOT	NMOT	NMOT
Maximum Power(Pmax/W)	365	369	374	378	382
Open Circuit Voltage(Voc/V)	41.00	41.20	41.40	41.60	41.80
Short Circuit Current(Isc/A)	11.49	11.55	11.61	11.66	11.72
Maximum Power Voltage(Vmp/V)	33.80	34.00	34.20	34.40	34.60
Maximum Power Current(Imp/A)	10.82	10.88	10.93	10.99	11.04

* Nominal Module Operating Temperature (NMOT): Irradiance 800W/m², AM 1.5, ambient temperature 20°C, wind speed 1 m/s. Power measurement tolerance: ±3%.

OPERATING PARAMETERS

Operating Temperature Range	-40°C~+85°C
Power Output Tolerance	0~3%
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	25A
Nominal Module Operating Temperature	45±2°C
[T98]max	≤70°C
Protection Class	Class II
Fire Rating	IEC Class C

MECHANICAL LOADING

Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Hailstone Test	25mm Hailstone at the speed of 23m/s

TEMPERATURE RATINGS (STC)

Temperature Coefficient of Isc	+0.04%/°C
Temperature Coefficient of Voc	-0.23%/°C
Temperature Coefficient of Pmax	-0.28%/°C

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.
©2026 Horay Solar Co.,Ltd. All rights reserved.
Specifications included in this datasheet are subject to change without notice.
Version number: HS182-TC-2026-A1

YouTube FaceBook Linkedin WeChat